

1

2

3

4

A

A

TRAFFIC FLOW

1XD7 PIN EACH SIDE

1XD7 PIN EACH SIDE

ANCHOR SPACING

1.28 m

48.15 m BETWEEN PINS

CONTINUATION OF STD 3.9m UNITS


B

B

TRAFFIC FLOW

3.9 m

11 DEFENDER UNITS



C

C

FEMALE END

MALE END

D10 PIN

**CONNECTION DETAIL-STEP 1**  
ORIENTATE FEMALE END TO MALE END

**CONNECTION DETAIL-STEP 2**  
SLIDE MALE END ONTO FEMALE


**CONNECTION DETAIL-STEP 3**  
INSERT THE PIN

Tolerances unless otherwise stated  
 Machining: up to 300mm ±0.50  
                   300 to ~ ±0.80  
 Fabrication: up to 300mm ±2.00  
                   300 to 1000mm ±3.00  
                   1000 to ~ ±6.00  
 Angular: all ±2.0°

MATERIAL  
 FINISH  
 WEIGHT  
 DIMENSIONS  
 DATE

MM

**SAFE BARRIERS**



SHEET 1 of 1

DRAWING DESCRIPTION  
 DRAWING REF.  
 DRAWN BY

DEFENDER D100HC SYSTEM  
 INSTALLATION DETAILS

DC CHECKED RM APPROVED RH

| REV | DATE | DESCRIPTION | DRAWN | APPRD. |
|-----|------|-------------|-------|--------|
|     |      |             |       |        |

1

2

3

4